

A fuel economy, fully synthetic motor oil, developed according to the most recent technology, based on specially selected fully synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- lower fuel consumption
- reduced formation of combustion residues (mid SAPS)
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming
- dark green color

## Performance

- ACEA C5
- FIAT: 9.55535-DM1
- PORSCHE: C20
- API SN, SN+
- VW 508.00/509.00

## Applications

This fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. This oil can only be used in engines which prescribe an oil with the specification VW 508.00/509.00.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.832
Viscosity 40 °C	mm <sup>2</sup> /s	39.30
Viscosity 100 °C	mm <sup>2</sup> /s	7.93
Viscosity index		179
Flash point COC	°C	220
Pour point	°C	-57
Total Base Number	mgKOH/g	8.3
Sulphated Ash	%	0.78