

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is extremely fuel-efficient and meets the requirements of the new Ford EcoBoost petrol engines. It ensures a reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission. It has excellent cold starting behavior giving a very good operating reliability.

Performance

- ACEA: A1 / B1 / C5
- API: SN
- FORD: WSS-M2C948-B
- JAGUAR / LAND ROVER STJR.03.5004

Features

Total engine protection : performance in keeping the engine clean.
 Fuel economy : superior fuel economy and CO2 reduction.
 Cold start : excellent fluidity at low temperature.

Applications

Meets the requirements of the Ford WSS-M2C948-B specification and is mandatory for Ford EcoBoost 1.0 3-cylinder engines and is required for further EcoBoost petrol engines. This oil can also be used where the vehicle manufacturer specifies a motor oil ACEA A1/B1 or API SN.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.851
Viscosity -20 °C	mPas	5500
Viscosity 40 °C	mm ₂ /s	42.3
Viscosity 100 °C	mm ₂ /s	7.9
Viscosity index		162
Flash point COC	°C	220
Pour point	°C	-39
Total Base Number	mgKOH/g	7.6
Sulphated Ash	%	0.8