

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

## Performance

- API: SP Resource Conserving
- ILSAC: GF-6A
- GM: DEXOS 1 (TM) GEN 3
- FORD: WSS-M2C946-A
- FORD: WSS-M2C961-A1
- API SQ Resource Conserving
- ILSAC GF-7A
- CHRYSLER: MS6395
- FORD: WSS-M2C946-B1

## Applications

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1 ? Gen 2

Characteristics	Unit	Average
Density at 15 °C	kg/l	0,851
Viscosity -30 °C	mPas	4140
Viscosity 40 °C	mm <sub>2</sub> /s	61,80
Viscosity 100 °C	mm <sub>2</sub> /s	11,30
Viscosity index		179
Flash point COC	°C	224
Pour point	°C	-30
Total Base Number	mgKOH/g	8,5
Sulphated Ash	%	0,89