

A fuel economy SAE 0W20 motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a high fuel economy
- a high and stable viscosity index
- a good resistance against shearing
- a very fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Performance

- ACEA: A1 / B1 / C5
- VOLVO: VCC RBS0-2AE

Applications

A fuel economy, specially formulated engine oil suitable for petrol and diesel engines of Volvo cars where the manufacturer prescribes a product that meets the specification VCC RBS0-2AE with viscosity SAE 0W20.

| Characteristics | Unit | Average |
|-------------------|--------------------|---------|
| Density at 15 °C | kg/l | 0.843 |
| Viscosity -35 °C | mPas | 5570 |
| Viscosity 40 °C | mm ₂ /s | 45.90 |
| Viscosity 100 °C | mm ₂ /s | 8.70 |
| Viscosity index | | 173 |
| Flash point COC | °C | 220 |
| Pour point | °C | -45 |
| Total Base Number | mgKOH/g | 7.7 |
| Sulphated Ash | % | 0.80 |