

This is a mineral lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

## Performance

- ALLISON : C4
- GM: DEXRON III-H
- MB: 236.5
- VOITH: H55.6335
- ZF: TE-ML 09B
- ZF: TE-ML 14A
- FORD: MERCON
- MAN: 339 V1/Z1
- MB: 236.1
- VOLVO: 97341
- ZF: TE-ML 11B

## Features

Frictional properties : smooth shift performance.

Anti-wear protection : extended transmission life.

Extended oil life : excellent thermal and oxidation stability.

## Applications

This oil is used in automatic transmissions, torque converters, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.855
Viscosity -40 °C	mPas	17500
Viscosity 40 °C	mm <sub>2</sub> /s	33.9
Viscosity 100 °C	mm <sub>2</sub> /s	7.1
Viscosity index		179
Flash point COC	°C	196
Pour point	°C	-45
Color		RED