

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

Performance

- AML: 4G4319A509/AA/S
- BMW: 83220142516
- HYUNDAI: 040000C90SG
- LAND ROVER: TYK500050
- VW: G 055 005
- BENTLEY: PY112995PA
- BMW: M-1375.4
- JAGUAR: Fluid 8432
- MASERATI: 231603
- ZF: TE-ML 11

Features

Anti-wear protection : significantly extended transmission life.
Frictional properties : very smooth gear shifting, no vibration.
Extended oil life : excellent thermal and oxidation stability.

Applications

Mainly intended for the ZF-6 speed automatic transmissions, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.845
Brookfield viscosity at -40 °C	mPas	9500
Viscosity 40 °C	mm ₂ /s	31.0
Viscosity 100 °C	mm ₂ /s	6.2
Viscosity index		153
Flash point COC	°C	202
Pour point	°C	-48
Color		AMBER