

This is a full synthetic lubricant based on carefully selected very high quality base oils with low viscosity, used in manual gearboxes of passenger cars, which allows to achieve the highest fuel economy. It offers optimized cold start properties and stable viscosity/temperature behavior.

## Performance

- API: GL-4
- BMW: MTF LT-3
- GM: MTF 0063
- PSA: B71 9730 A8
- VW: G 052 178 (G 052 178 A2)
- VW: G 052 726 (G 052 726 A2/ G 055 726 A2 / G 060 726 A2/ G 070 726 A2)
- BMW: MTF LT-2
- FORD: WSS-M2C200-D2
- NISSAN: LV MTF-1
- VW: G 052 171 (G 052 171 A1/A2)
- VW: G 052 512 (G 052 512 A2)
- VW: G 052 798

## Features

Anti wear protection: significantly extended transmission life.

Frictional properties: very smooth gear shifting, no vibration.

Extended oil life: excellent thermal and oxidation stability.

## Applications

This product is specifically formulated for gearboxes for which low viscosity manual transmission fluids are recommended, e.g. VW Gear Oil SAE 75W.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.842
Viscosity -40 °C	mPas	7000
Viscosity 40 °C	mm <sub>2</sub> /s	30.5
Viscosity 100 °C	mm <sub>2</sub> /s	6.2
Viscosity index		157
Flash point COC	°C	220
Pour point	°C	-57