

This is a fully synthetic lubricant based on carefully selected highly refined base oils. This is a high performance transmission oil for all differentials, including those equipped with a "limited slip" mechanism. It is characterized by an exceptionally high viscosity stability at different temperatures and a very high fluidity at low temperature.

## Performance

- API: GL 4+, GL-5 / LS
- BMW MSP/A
- MAN 341 Z2, 341 E3, 342 M3
- ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, 19C, 21B
- VOITH 3.325-340
- INTERNATIONAL TMS-6816
- MIL: MIL-L-2105 E
- SCANIA STO 1.0 box
- MB 235.8
- IVECO axles
- Arvin Meritor O-76N
- DAF

## Features

Frictional properties : very smooth gear shifting, no vibration.

Anti-wear protection : extended transmission life.

Extended oil life : excellent thermal and oxidation stability.

## Applications

This product is used in highly loaded axles and reduction gears of cars, trucks and off-road equipment. It has "limited-slip" characteristics, and is specifically recommended for 4X4 vehicles.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.905
Viscosity 40 °C	mm <sup>2</sup> /s	170
Viscosity 100 °C	mm <sup>2</sup> /s	26.5
Viscosity index		195
Flash point COC	°C	160
Pour point	°C	-51