

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives

## Performance

- AFNOR: NF E 48-603 HM
- AFNOR: NF E 48-690
- AFNOR: NF E 48-691
- CINCINNATI: MACHINE P-69 (ISO 68)
- DENISON: HF-2 HLP
- DIN: 51524 Part 2
- EATON VICKERS: I-286-S
- EATON VICKERS: M-2950-S
- ISO: 11158, HM
- ISO: 6743-4, HM

## Applications

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

Characteristics	Unité	Moyenne
Densité @ 15 °C	kg/l	0.876
Viscosité 40 °C	mm <sup>2</sup> /s	68.00
Viscosité 100 °C	mm <sup>2</sup> /s	8.7
Indice de viscosité		102
Point d'éclair COC	°C	220
Point d'écoulement	°C	-25
Alcalinité	mgKOH/g	0.40
Cendres sulfatées	%	0.06