

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agriculture tractors.

## Performance

- ACEA: E3
- ALLISON : C4 (Agriculture applic.)
- API: GL 4
- API: SF/CE
- CASE: MAT 3526
- FORD: ESN-M2C134 C/D
- FORD: FNH 82009202
- JD: J27
- MF: M 1139
- MF: M 1144
- NH: NH 030C
- ZF: TE-ML 05K
- ZF: TE-ML 06B
- ZF: TE-ML 07B
- AFNOR: NF E 68-603 E
- API: CG-4
- API: GL 5 (Low speed/high torque)
- CASE: MAT 3525
- EATON VICKERS:M-2950-S
- FORD: ESN-M2C159 B/C
- JD: J20C
- MF: M 1135
- MF: M 1143
- MF: M 1145
- ZF: TE-ML 03A
- ZF: TE-ML 06A
- ZF: TE-ML 06C
- ZF: TE-ML 07D

## Features

Anti-wear and oxidation stability : proven protection of critical parts.

## Applications

This multigrade oil is advised for the lubrication of charged and uncharged diesel engines, 4-stroke gasoline and LPG-engines. This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines of off-highway equipment.

Characteristics	Unit	Media
Densità a 15 ° C	kg/l	0.874
Viscosità -20 ° C	mPas	6600
Viscosità 40 ° C	mm <sup>2</sup> /s	81.7
Viscosità 100 ° C	mm <sup>2</sup> /s	10.8
Indice di viscosità		118
Punto di infiammabilità COC	°C	222
Punto di scorrimento	°C	-36